

Panel labels

self adhesive, precut

The MG-SIGNS labels is used for in-house production of warning, hazard, prohibition and mandatory signs from pictograms provided in the library of GENIUSPRO software. A highly versatile system for rapidly and accurately producing signs in all languages, on a one-off basis if required.

MG-SIGNS



MG-SIGNS-VY

Material: PVC film; the colours white PVC99008WH and yellow PVC99008YE are UL approved.

Operating temperature range: -30°C (-22°F) to +70°C (+158°F)

Application temperature range: +10°C (+50°F) to +40°C (+104°F)



Family	Shape	Size mm	Type			Ø mm Holes	Labels per sheet	Quantity	SW code
			white PVC99008WH	yellow PVC99008YE	red				
MG-SIGNS-VY		50		990700N			4	200	241
		100		990701			1	50	242
		50		990857			4	200	260
		Ø 25	990860	990859	990992	12	600	236	
	Ø 100		990702	990866		1	50	238	
		37 x 74		990709	990988	2	100	246	
		52 x 105	990825	990710		2	100	247	
		62		990740		22,5	1	50	232
		90		990741		22,5	1	50	233
		90		990742		30,5	1	50	234
	45 x 150	990991				2	100	275	

MG-SIGNS-PY

Material: Polyester film; the colour metallic grey PET99005GY is UL approved.

Operating temperature range: -40°C (-40°F) to +130°C (+266°F)

Application temperature range: +10°C (+50°F) to +40°C (+104°F)



Family	Shape	Size mm	Type metallic grey PET99005GY	Ø mm Holes	Tags per sheet	Quantity	SW code
MG-SIGNS-PY		46 x 46	47826	24	4	200	230

Directly on suitable surfaces.



template with PET support.....page 10
ribbons.....page 11