

MG-SAT

THERMAL TRANSFER SYSTEM FOR SHEET MEDIA

Security labels

ultradestructible and antitamper film, precut

MG-SAT-V “Void” anti tamper film: when removed, leaves the word “Void” on the surface, as evidence of its removal.

MG-SAT-C “Checker-board” anti tamper film: when removed, leaves behind a checker-board imprint on the surface, as evidence of its removal.

MG-SAT-D Ultradestructible film: when removed, allowing two hours after application, this film will break up into very small fragments to prevent replacement.



Material: matt Polyester film

Operating temperature range: -40°C (-40°F) to +140°C (+284°F)

PET SF 40°C 90°C



Family	Size mm	Type white	Tags per sheet	Quantity	SW code
MG-SAT-V	20 x 62	29004	10	500	615
	24 x 38	29001	6	300	270
	37 x 74	29002	2	100	271
	52 x 105	29003	2	100	272

Material: matt Polyester film

Operating temperature range: -40°C (-40°F) to +140°C (+284°F)

PET SF 40°C 140°C



Family	Size mm	Type metallic grey	Tags per sheet	Quantity	SW code
MG-SAT-C	9 x 15	29806	70	3.500	161
	15 x 49	29807	14	700	187
	24 x 38	29801	6	300	270
	37 x 74	29802	2	100	271
	52 x 105	29803	2	100	272
MG2-SAT-C	110 x 140	29804	1	50	273

Material: film PE-HD

Operating temperature range: -30°C (-58°F) to +80°C (+230°F)

PEHD SF 30°C 80°C



Family	Size mm	Type white	Tags per sheet	Quantity	SW code
MG-SAT-D	9 x 15	29906	70	3.500	161
	15 x 49	29907	14	700	187
	24 x 38	29901	6	300	270
	37 x 74	29902	2	100	271
	52 x 105	29903	2	100	272



Directly on suitable surfaces.

template with PET support.....page 10
ribbons.....page 11