

MG-DOG



Material: Polycarbonate, Halogen Free, self extinguishing class V0: UL94; the colours white PC10050WH and yellow PC10050YE are EN 45545-2 approved.

Operating temperature range: -40°C (-40°F) to +130°C (+266°F)

Application temperature range: +10°C (+50°F) to +40°C (+104°F)



	Size mm	Type			Ø hole mm	Cable tie max. mm	Tags per sheet	Quantity	SW code
		white PC10050WH	yellow PC10050YE	green					
	25 x 50	48204-HF			5	4,8	8	400	868
	52 x 107	48397-HF			6,5	4,8	2	100	204
	Ø 20	48392-HF		48352-HF	6,5	4,8	12	300	875
	Ø 35	48300-HF	48340-HF		4	3,6	6	300	870

Material: SBS Styrene-Butadiene-Styrene, Halogen free, self extinguishing class HB: UL94

Operating temperature range: -30°C (-22°F) to +70°C (+158°F)



	Size mm	Type white	Ø hole mm	Cable tie max. mm	Tags per sheet	Quantity	SW code
	19 x 38	40205-SBS	8	8	8	400	869
	21 x 39	40206-SBS	12,7	8	8	400	873

Appropriate attachment.
Use the 991611 ribbon to print Polycarbonate items.



template with PET support.....page 10
ribbons.....page 11
cable ties.....page 128

