

MG-VRT-RH

THERMAL TRANSFER SYSTEM FOR SHEET MEDIA

Panel plates rivet fixing with holes

customisable

MG-VRT-RH rigid PVC panel plates are used to create name plates, rating plates, data plates using company logos, technical data, serial numbers, EC certification, etc. Transparent Polycarbonate covers can be used for increased durability.

Consult us for availability of other colours and transparent versions.

Note: UV resistance may vary between colours.



Material: Rigid PVC, self extinguishing class V0: UL94; the colours white PVC10050WH and yellow PVC10050YE are UL approved.

Operating temperature range: -30°C (-22°F) to +60°C (+140°F)

Application temperature range: +10°C (+50°F) to +40°C (+104°F)



Size mm	Type						No. Holes	Tags per sheet	Quantity	SW code
	white PVC10050WH	yellow PVC10050YE	grey	red	blue	black				
15 x 35	49906					49916	2	21	1.050	837
15 x 52	48924					48129	2	14	350	831
15 x 80	48938	48438				48138	2	7	175	828
25 x 50	48906	48406	48806GY		48606		2	8	200	860
25 x 75	48907	48407					2	4	100	809
25 x 80	48931					48131	2	4	100	832
25 x 100	48914	48414				48114	2	4	200	206
29 x 140	48932					48132	2	3	75	834
35 x 50	48930					48130	4	6	150	833
35 x 80	48937	48437		48237	48637		2	3	75	827
35 x 100	48909	48409					2	3	75	818
35 x 142	48923						2	3	150	835
50 x 100	48911	48411	48811GY				4	2	50	811
50 x 140	48919						4	2	50	872
60 x 100	48927						4	2	50	842
75 x 120	48915	48415		48215		48115	4	1	50	816
82 x 142	48921	48421					4	1	50	836
105 x 110	48912	48412	48712GY				4	1	25	859



Directly on suitable surfaces.

template with PET support.....page 10
ribbons.....page 11